

Rubiomonocoat MAINTENANCE OIL

DESCRIPTION:

Rubio Monocoat Maintenance Oil is a ready-to-use product that was developed to care for parquet floors treated with **Rubio Monocoat Oil Plus**. This treatment restores and intensifies both the colour and the durability of the floor. Intervals for maintaining the floor vary according to how much wear the floor is getting. It is recommended that this treatment be carried out just before the protective oil, **Rubio Monocoat Oil Plus**, shows signs of fading. Available in the full range of **Rubio Monocoat Oil Plus** complimentary colours.

INSTRUCTIONS:

No professional expertise is required to treat your floor with **Rubio Monocoat Maintenance Oil**.

1. Eliminate dirt and dust from the floor.
2. Clean the floor thoroughly with **Rubio Monocoat Soap** and water. Rinse well with water to eliminate any soap residues. Leave it to dry completely.
3. Apply **Rubio Monocoat Maintenance Oil** with a cloth, a brush or a sponge, preferably in sections of 2 to 4 m². Each treated section should be wiped dry with a paper towel within 15 minutes. If a floor polisher is used, carry out this treatment using a lint-free cotton cloth.
4. Ensure the room is well-ventilated. The floor should be dry after 6 - 8 hours.

The floor can be cleaned with a cloth dampened with water after 48 hours. Do not use soap at this stage! Wait 1 week before once more maintaining the floor with a mixture of **Rubio Monocoat Soap** (matt) or **Rubio Monocoat Soap Satin** (satin gloss) and water.

COVERAGE:

0,5 l = 75 – 100 m² (depending on wear)

Use very little product to prevent the floor from becoming sticky.

NOTE: In cases of exceptional wear it may not be possible to restore the original colour. We recommend having the floor restored by a skilled fitter using the original **Rubio Monocoat Oil Plus**.

TECHNICAL SPECIFICATIONS:

Basis: a mixture of natural oils and hard wax

Colour: 35 standard colours

Consistency: liquid

Flash point cc (astm d93): > 62°C

Fixed dust percentage: > 72 %

Density: Pure: 0.93 g/cm³ - 0 colours: 1 to 1.4 g/cm³

VOC: 280 g/l

STORAGE:

The product can be stored for up to 12 months. Store in dry conditions and in the original packaging.

PACKAGING:

0,5 l can.

WARNING:

The product may NOT be diluted!
Cloths, saturated with oil, may spontaneously combust.
After usage, they need to be soaked in water before disposal.

PROVIDED BY:

These guidelines are the result of tests and our own experience and are provided in good faith. Since we have no control over individual circumstances, we cannot be held responsible for any damage incurred as a result of incorrect or inappropriate use of said guidelines.

Consult the safety sheet before use.

MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.

Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823
info@muyllefacon.be - www.rubiomonocoat.com

